



FI 114 fiamma

Sorgente Luminosa **LED EPISTAR SMD**
 Temperatura d'esercizio -20°C + 50°C
 Destinazione d'uso **Interno**
 Materiali **Policarbonato/Alluminio**

Vac
220-240



codice	W potenza	W equilavenza	K colore	lumen	CRI	quote (L x H)
FI 114 BC	4	40	3000	320	>80	37 - 103



GO 120 goccia

Sorgente Luminosa **LED EPISTAR SMD**
 Temperatura d'esercizio -20°C + 50°C
 Destinazione d'uso **Interno**
 Materiali **Policarbonato/Alluminio**

Vac
220-240



codice	W potenza	W equilavenza	K colore	lumen	CRI	quote (L x H)
GO 120 BC	10	60	3000	810	>80	60 - 108
GO 120 BN	10	60	4000	820	>80	60 - 108
GO 120 BF	10	60	6000	840	>80	60 - 108



GO 122 goccia

Sorgente Luminosa **LED EPISTAR SMD**
 Temperatura d'esercizio -20°C + 50°C
 Destinazione d'uso **Interno**
 Materiali **Policarbonato/Alluminio**

Vac
220-240



codice	W potenza	W equilavenza	K colore	lumen	CRI	quote (L x H)
GO 122 BC	12	75	3000	1055	>80	60 - 118
GO 122 BN	12	75	4000	1075	>80	60 - 118
GO 122 BF	12	75	6000	1100	>80	60 - 118



GL 126 globo

Sorgente Luminosa **LED EPISTAR SMD**
 Temperatura d'esercizio -20°C + 50°C
 Destinazione d'uso **Interno**
 Materiali **Policarbonato/Alluminio**

Vac
220-240



codice	W potenza	W equilavenza	K colore	lumen	CRI	quote (L x H)
GL 126 BC	16	100	3000	1250	>80	120 - 163
GL 126 BN	16	100	4000	1350	>80	120 - 163
GL 126 BF	16	100	6000	1450	>80	120 - 163